

06-4005 Series

Models: 06-4005-0511, 06-4005-0800, 06-4005-3611

Standard Features:

- 2 qt (1.9 l) steel reservoir
- 2 micron filtration (Beta rating > 1000 @ 4 µm per ISO 4572)
- Shut off valve (zero leakage)
- Single stage manual hand pump
- Stroke displacement .58 in³/stroke
- Relief set 3,250 psi
- Pressure gauge 5,000 psi (345 bar)
- 15 ft (4.6 m) #4 hose with 37° JIC female swivel connector
- Finish: Durable Powder Coat Tronair Blue



06-4035, 06-5004, 06-5040 and 06-5041 Series

NSN: 4920-01-578-3125 - for model 06-4035-0500

Models: 06-4035-0500, 06-4035-0800, 06-4035-3600
06-5004-0500, 06-5004-0800, 06-5004-3600
06-5040-0510, 06-5040-0800, 06-5040-3600
06-5041-0500, 06-5041-0800, 06-5041-3610

Standard Features:

- 8 gal (30 l) polyethylene reservoir
- 15 ft (4.6 m) #4 hose with 37° JIC female swivel connector
- Shut off valve for static testing
- 2 micron filtration (Beta rating > 2000 per ISO 4572)
- Dual stage manual hand pump
- Stroke displacement
2.1 in³/stroke to 500 psi
.4 in³/stroke to 5,000 psi
- 8 in (20 cm) semi-pneumatic tires
- Dual hose selector valve standard on 06-5004 and 06-5041 series only
- Sturdy welded steel construction
- Finish: Durable Powder Coat Tronair Blue



Tronair, Inc. - 1740 Eber Road, Holland, Ohio 43528, USA

Email: sales@tronair.com • Fax: 419-867-0634

Phone: 419-866-6301 • Toll Free: 1-800-426-6301

Asia Sales Offices

China - Email: tronairchina@tronair.com • Phone: 86-592-5560735 • Fax: 86-592-5563132

Asia/Australia - Email: tronairasia@tronair.com • Phone: 662 2121463 • Fax: 662 2121332

Europe, Middle East and Africa Sales Office

Email: saleseurope@tronair.com • Phone: 44-0-113-245-3300 • Fax: 44-0-113-322-0436

06-5009 and 06-5010 Series

Models: 06-5009-6500, 06-5009-6600, 06-5009-6800
06-5010-6500, 06-5010-6600, 06-5010-6800

Standard Features:

- 2 micron filtration (Beta rating > 1000 @ 4 µm per ISO 4572)
- 15 ft (4.6 m) #6 hose with 37° JIC female swivel connector
- Sturdy steel construction
- 100 psi (6.9 bar) certified pressure gauge
- 125 psi (8.6 bar) safety pop off valve
- Shut off valve and filler tube
- 8 in (20 cm) semi-pneumatic tires

06-5009-Series



06-5021 Series

Models: 06-5021-1500, 06-5021-1800, 06-5021-3600

Standard Features:

- Pump directly from 5 U.S. gallon container
- 2 micron filtration (Beta rating > 1000 @ 4 µm per ISO 4572)
- 15 ft (4.6 m) #6 hose with 37° JIC female swivel connector
- Sturdy steel construction
- 200 psi (13.8 bar) maximum pressure
- High displacement hand pump (13 strokes per quart)
- 06T5021-1500 and 06T5021-3600 adds a Totalizer to unit
- Finish: Durable Powder Coat Tronair Blue

06-5021-Series



06-5022 Series

Models: 06-5022-6500, 06-5022-6600, 06-5022-6800

Standard Features:

- 2 micron filtration (Beta rating > 1000 @ 4 µm per ISO 4572)
- 15 ft (4.6 m) #6 hose with 37° JIC female swivel connector
- Sturdy steel construction
- 2 in (5 cm) filler port
- High displacement hand pump (13 strokes per quart)
- Hose storage bracket

06-5022-Series



06-5042-Series

06-5042 Series

Models: 06-5042-0500, 06-5042-0800, 06-5042-3600

Standard Features:

- 2 micron filtration (Beta rating > 1000 @ 4 µm per ISO 4572)
- 15 ft (4.6 m) #6 hose with 37° JIC female swivel connector
- Sturdy steel construction
- High displacement hand pump (13 strokes per quart)
- 8 in (20 cm) semi-pneumatic tires
- Finish: Durable Powder Coat Tronair Blue

06-5024 Series

Models: 06-5024-3510, 06-5024-3610, 06-5024-3800
06T5024-3510, 06T5024-3610, 06T5024-3800

- Attaches to any 55 U.S. gallon drum
- 2 micron filtration (Beta rating > 1000 @ 4 µm per ISO 4572)
- 15 ft (4.6 m) #6 hose with 37° JIC female swivel connector
- Sturdy steel construction
- 100 psi (6.9 bar) maximum pressure
- 14 gpm maximum flow
- Shut off valve
- Operates off shop air
- Optional drum dolly (H-1726)
- Finish: Durable Powder Coat Tronair Blue



06-5024-Series

06-5025 Series

Models: 06-5025-1512, 06-5025-3610

Standard Features:

- 2 micron filtration (Beta rating > 1000 @ 4 µm per ISO 4572)
- 15 ft (4.6 m) #6 hose with 37° JIC female swivel connector
- Sturdy steel construction
- 100 psi (6.9 bar) maximum pressure
- 14 gpm maximum flow
- 68 gal (257 l) capacity
- High displacement pneumatic pump driven by self-contained nitrogen bottle and shut-off valve
- Front wheels lock with towbar in upright position
- Finish: Durable Powder Coat Tronair Blue



06-5025-Series

06-5043 Series

Models: 06-5043-1500, 06-5043-1800,
06-5043-3600

Standard Features:

- 2 micron filtration (Beta rating > 1000 @ 4 µm per ISO 4572)
- 15 ft (4.6 m) #6 hose with 37° JIC female swivel connector
- Sturdy steel construction
- 16 gauge sheet metal weather proof cabinet
- High displacement hand pump (13 strokes per quart)
- Front wheels lock with towbar in upright position
- 10 in (25 cm) pneumatic tires
- Finish: Durable Powder Coat Tronair Blue

06-5043-Series

