


These test procedures shall be complied to, without exception, annually.

Model Number _____ Serial Number _____

Tested By _____ Date _____

Inspected By _____ Date _____

1. Measure distance 1 and 2 at two points and mark measurement location
2. Load arm weldments into a test fixture. Apply downward force on each arm, at arm end point through adaptor end point, 1 ½ times engine load and hold for approximately 1 minute. Remove from fixture and inspect for any signs of failure (i.e.: broken or cracked welds, elongated holes, or crack in any portion of the component). Any item, which does not successfully pass the test, is to be rejected and discarded or returned to Tronair for evaluation.
3. Re-measure distance 1 and 2 at the two points. If distance is different from original measurement contact Tronair for evaluation.



DISTANCE 1	
BEFORE	AFTER

DISTANCE 2	
BEFORE	AFTER

LOAD APPLIED	

www.tronair.com

Tronair • Email: sales@tronair.com • Phone: 419-866-6301 or 800-426-6301 • Fax: 419-867-0634

Asia Sales Offices: China - Email: tronairchina@tronair.com • Phone: 86-592-5560735 • Fax: 86-592-5563132

Asia/Australia - Email: tronairasia@tronair.com • Phone: 662 2121463 • Fax: 662 2121332

Europe, Middle East & Africa Sales Office • Email: sales@tronair.com • Phone: 44-0-113-245-3300 • Fax: 44-0-113-322-0436

TR020514