

Hydraulic Power Units - Ordering Instructions

- Step 1** – Determine the size of the Hydraulic Power Unit required. Check the aircraft maintenance manual, or refer to Tronair's Aircraft Tool and Equipment list at tronair.com
- Step 2** – Select the correct fluid type that matches your aircraft
- Step 3** – Determine if the unit requires a CE mark and/or an Electric Soft Start (call for soft start availability)
- Step 4** – Choose a paint color from the available colors
- Step 5** – Select quick disconnect couplings to attach the hoses to the aircraft bulkhead fittings. These couplings will become part of the model number sequence, they are attached to hose ends upon receipt
- Step 6** – Determine the input voltage the Hydraulic Power Unit will be operating at. **When ordering, the most common error is selecting incorrect input voltages** (To check input voltage, measure from L1 to L2, L1 to L3, and L2 to L3. The highest voltage obtained from these readings is the correct input voltage)
- Step 7** – Select additional features to customize your unit. We offer a broad range of options to enhance your Hydraulic Power Unit to your particular needs or budget. Options listed in the chart must be in alphabetical order. Refer to the option matrix (below) for standard features per model number

MANDATORY INFORMATION								OPTIONS (alphabetical order)																																																																																																																																																																																													
5																																																																																																																																																																																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>char</th> <th>build</th> </tr> <tr> <td>1</td> <td>CE Compliant</td> </tr> <tr> <td>3</td> <td>CE Soft Start</td> </tr> </table>								char	build	1	CE Compliant	3	CE Soft Start	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>char</th> <th>fluid</th> </tr> <tr> <td>1</td> <td>MIL-PRF-5606</td> </tr> <tr> <td>2</td> <td>MIL-PRF-83282</td> </tr> <tr> <td>3</td> <td>Phosphate Ester (Skydrol)</td> </tr> <tr> <td>4</td> <td>MIL-PRF-87257</td> </tr> <tr> <td>5</td> <td>Phosphate Ester (HyJet V)</td> </tr> </table>								char	fluid	1	MIL-PRF-5606	2	MIL-PRF-83282	3	Phosphate Ester (Skydrol)	4	MIL-PRF-87257	5	Phosphate Ester (HyJet V)	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>char</th> <th>voltage/freq/phase</th> <th>input cord</th> </tr> <tr> <td>0</td> <td>208V/60Hz/3PH</td> <td rowspan="9">50 ft (15.2 m) input cord length</td> </tr> <tr> <td>1</td> <td>230V/60Hz/3PH</td> </tr> <tr> <td>2</td> <td>380V/60Hz/3PH</td> </tr> <tr> <td>3</td> <td>460V/60Hz/3PH</td> </tr> <tr> <td>4</td> <td>575V/60Hz/3PH</td> </tr> <tr> <td>5</td> <td>200V/50Hz/3PH</td> </tr> <tr> <td>6</td> <td>220V/50Hz/3PH</td> </tr> <tr> <td>7</td> <td>380V/50Hz/3PH</td> </tr> <tr> <td>8</td> <td>415V/50Hz/3PH</td> </tr> <tr> <td>9</td> <td>440V/50Hz/3PH</td> </tr> <tr> <td>Q</td> <td>208V/60Hz/3PH</td> <td rowspan="9">100 ft (30.5 m) input cord length</td> </tr> <tr> <td>R</td> <td>230V/60Hz/3PH</td> </tr> <tr> <td>S</td> <td>380V/60Hz/3PH</td> </tr> <tr> <td>T</td> <td>460V/60Hz/3PH</td> </tr> <tr> <td>U</td> <td>575V/60Hz/3PH</td> </tr> <tr> <td>V</td> <td>200V/50Hz/3PH</td> </tr> <tr> <td>W</td> <td>220V/50Hz/3PH</td> </tr> <tr> <td>X</td> <td>380V/50Hz/3PH</td> </tr> <tr> <td>Y</td> <td>415V/50Hz/3PH</td> </tr> <tr> <td>Z</td> <td>440V/50Hz/3PH</td> </tr> <tr> <td>E</td> <td>220V/50Hz/1 Phase**</td> <td>15 ft</td> </tr> <tr> <td>F</td> <td>120V/60Hz/1 Phase**</td> <td>(4.6 m)</td> </tr> </table> <p style="text-align: center;">**available on 5Z only</p>								char	voltage/freq/phase	input cord	0	208V/60Hz/3PH	50 ft (15.2 m) input cord length	1	230V/60Hz/3PH	2	380V/60Hz/3PH	3	460V/60Hz/3PH	4	575V/60Hz/3PH	5	200V/50Hz/3PH	6	220V/50Hz/3PH	7	380V/50Hz/3PH	8	415V/50Hz/3PH	9	440V/50Hz/3PH	Q	208V/60Hz/3PH	100 ft (30.5 m) input cord length	R	230V/60Hz/3PH	S	380V/60Hz/3PH	T	460V/60Hz/3PH	U	575V/60Hz/3PH	V	200V/50Hz/3PH	W	220V/50Hz/3PH	X	380V/50Hz/3PH	Y	415V/50Hz/3PH	Z	440V/50Hz/3PH	E	220V/50Hz/1 Phase**	15 ft	F	120V/60Hz/1 Phase**	(4.6 m)	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>char</th> <th>description</th> </tr> <tr> <td>A</td> <td>25 ft hoses</td> </tr> <tr> <td>B</td> <td>50 ft hoses</td> </tr> <tr> <td>AA</td> <td>25 ft hoses (split system)</td> </tr> <tr> <td>BB</td> <td>50 ft hoses (split system)</td> </tr> <tr> <td>C</td> <td>split system</td> </tr> <tr> <td>D</td> <td>split system w/crossover check</td> </tr> <tr> <td>E</td> <td>hourmeter (50HZ)</td> </tr> <tr> <td>F</td> <td>hourmeter (60HZ)</td> </tr> <tr> <td>G</td> <td>voltage monitor (200-230V)</td> </tr> <tr> <td>H</td> <td>voltage monitor (380V)</td> </tr> <tr> <td>I</td> <td>voltage monitor (415-460V)</td> </tr> <tr> <td>J</td> <td>voltage monitor (575V)</td> </tr> <tr> <td>K</td> <td>pyrometer</td> </tr> <tr> <td>L</td> <td>electric reservoir level</td> </tr> <tr> <td>M</td> <td>hand pump</td> </tr> <tr> <td>N</td> <td>towing/trailer package</td> </tr> <tr> <td>P</td> <td>reservoir overflow return</td> </tr> <tr> <td>Q</td> <td>calibration port</td> </tr> <tr> <td>R</td> <td>electric filter clogged indicator</td> </tr> <tr> <td>S</td> <td>electric over temperature</td> </tr> <tr> <td>T</td> <td>return back pressure w/sight gauge</td> </tr> <tr> <td>U</td> <td>return sight gauge</td> </tr> <tr> <td>V</td> <td>return back pressure</td> </tr> <tr> <td>W</td> <td>return filter** // contamination monitor***</td> </tr> <tr> <td>X</td> <td>height ext. cart** // 50 ft hand pump hose***</td> </tr> <tr> <td>Y</td> <td>return sight gauge (split system)</td> </tr> <tr> <td>Z</td> <td>no return valves (split system)</td> </tr> <tr> <td>1</td> <td>return back pressure (split system)</td> </tr> <tr> <td>2</td> <td>red stack light</td> </tr> <tr> <td>4</td> <td>drip pan</td> </tr> <tr> <td>5</td> <td>remote e-stop (50 ft)</td> </tr> <tr> <td>7</td> <td>hand pump (large displacement)</td> </tr> <tr> <td>8</td> <td>pressure reducing valve (split system)</td> </tr> </table> <p style="text-align: center;">** 50 series only // ***all other models</p>								char	description	A	25 ft hoses	B	50 ft hoses	AA	25 ft hoses (split system)	BB	50 ft hoses (split system)	C	split system	D	split system w/crossover check	E	hourmeter (50HZ)	F	hourmeter (60HZ)	G	voltage monitor (200-230V)	H	voltage monitor (380V)	I	voltage monitor (415-460V)	J	voltage monitor (575V)	K	pyrometer	L	electric reservoir level	M	hand pump	N	towing/trailer package	P	reservoir overflow return	Q	calibration port	R	electric filter clogged indicator	S	electric over temperature	T	return back pressure w/sight gauge	U	return sight gauge	V	return back pressure	W	return filter** // contamination monitor***	X	height ext. cart** // 50 ft hand pump hose***	Y	return sight gauge (split system)	Z	no return valves (split system)	1	return back pressure (split system)	2	red stack light	4	drip pan	5	remote e-stop (50 ft)	7	hand pump (large displacement)	8	pressure reducing valve (split system)																													
								char	build																																																																																																																																																																																												
1	CE Compliant																																																																																																																																																																																																				
3	CE Soft Start																																																																																																																																																																																																				
char	fluid																																																																																																																																																																																																				
1	MIL-PRF-5606																																																																																																																																																																																																				
2	MIL-PRF-83282																																																																																																																																																																																																				
3	Phosphate Ester (Skydrol)																																																																																																																																																																																																				
4	MIL-PRF-87257																																																																																																																																																																																																				
5	Phosphate Ester (HyJet V)																																																																																																																																																																																																				
char	voltage/freq/phase	input cord																																																																																																																																																																																																			
0	208V/60Hz/3PH	50 ft (15.2 m) input cord length																																																																																																																																																																																																			
1	230V/60Hz/3PH																																																																																																																																																																																																				
2	380V/60Hz/3PH																																																																																																																																																																																																				
3	460V/60Hz/3PH																																																																																																																																																																																																				
4	575V/60Hz/3PH																																																																																																																																																																																																				
5	200V/50Hz/3PH																																																																																																																																																																																																				
6	220V/50Hz/3PH																																																																																																																																																																																																				
7	380V/50Hz/3PH																																																																																																																																																																																																				
8	415V/50Hz/3PH																																																																																																																																																																																																				
9	440V/50Hz/3PH																																																																																																																																																																																																				
Q	208V/60Hz/3PH	100 ft (30.5 m) input cord length																																																																																																																																																																																																			
R	230V/60Hz/3PH																																																																																																																																																																																																				
S	380V/60Hz/3PH																																																																																																																																																																																																				
T	460V/60Hz/3PH																																																																																																																																																																																																				
U	575V/60Hz/3PH																																																																																																																																																																																																				
V	200V/50Hz/3PH																																																																																																																																																																																																				
W	220V/50Hz/3PH																																																																																																																																																																																																				
X	380V/50Hz/3PH																																																																																																																																																																																																				
Y	415V/50Hz/3PH																																																																																																																																																																																																				
Z	440V/50Hz/3PH																																																																																																																																																																																																				
E	220V/50Hz/1 Phase**	15 ft																																																																																																																																																																																																			
F	120V/60Hz/1 Phase**	(4.6 m)																																																																																																																																																																																																			
char	description																																																																																																																																																																																																				
A	25 ft hoses																																																																																																																																																																																																				
B	50 ft hoses																																																																																																																																																																																																				
AA	25 ft hoses (split system)																																																																																																																																																																																																				
BB	50 ft hoses (split system)																																																																																																																																																																																																				
C	split system																																																																																																																																																																																																				
D	split system w/crossover check																																																																																																																																																																																																				
E	hourmeter (50HZ)																																																																																																																																																																																																				
F	hourmeter (60HZ)																																																																																																																																																																																																				
G	voltage monitor (200-230V)																																																																																																																																																																																																				
H	voltage monitor (380V)																																																																																																																																																																																																				
I	voltage monitor (415-460V)																																																																																																																																																																																																				
J	voltage monitor (575V)																																																																																																																																																																																																				
K	pyrometer																																																																																																																																																																																																				
L	electric reservoir level																																																																																																																																																																																																				
M	hand pump																																																																																																																																																																																																				
N	towing/trailer package																																																																																																																																																																																																				
P	reservoir overflow return																																																																																																																																																																																																				
Q	calibration port																																																																																																																																																																																																				
R	electric filter clogged indicator																																																																																																																																																																																																				
S	electric over temperature																																																																																																																																																																																																				
T	return back pressure w/sight gauge																																																																																																																																																																																																				
U	return sight gauge																																																																																																																																																																																																				
V	return back pressure																																																																																																																																																																																																				
W	return filter** // contamination monitor***																																																																																																																																																																																																				
X	height ext. cart** // 50 ft hand pump hose***																																																																																																																																																																																																				
Y	return sight gauge (split system)																																																																																																																																																																																																				
Z	no return valves (split system)																																																																																																																																																																																																				
1	return back pressure (split system)																																																																																																																																																																																																				
2	red stack light																																																																																																																																																																																																				
4	drip pan																																																																																																																																																																																																				
5	remote e-stop (50 ft)																																																																																																																																																																																																				
7	hand pump (large displacement)																																																																																																																																																																																																				
8	pressure reducing valve (split system)																																																																																																																																																																																																				
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">char</th> <th colspan="2">60 Hz</th> <th colspan="2">50 Hz</th> <th rowspan="2">psi</th> <th rowspan="2">bar</th> <th rowspan="2">hp</th> <th rowspan="2">kW</th> </tr> <tr> <th>gpm</th> <th>lpm</th> <th>gpm</th> <th>lpm</th> </tr> </thead> <tbody> <tr><td>0</td><td>6</td><td>23</td><td>5</td><td>19</td><td>1800</td><td>124</td><td>3</td><td>2.2</td></tr> <tr><td>1</td><td>6</td><td>23</td><td>5</td><td>19</td><td>3000</td><td>207</td><td>5</td><td>3.7</td></tr> <tr><td>2</td><td>10</td><td>38</td><td>8</td><td>32</td><td>3000</td><td>207</td><td>15</td><td>11</td></tr> <tr><td>3</td><td>11</td><td>42</td><td>9</td><td>35</td><td>5000</td><td>345</td><td>25</td><td>19</td></tr> <tr><td>4</td><td>15</td><td>57</td><td>13</td><td>47</td><td>3500</td><td>241</td><td>25</td><td>19</td></tr> <tr><td>J</td><td>20</td><td>76</td><td>17</td><td>63</td><td>4000</td><td>276</td><td>30</td><td>22</td></tr> <tr><td>5</td><td>25</td><td>95</td><td>21</td><td>79</td><td>5000</td><td>345</td><td>75</td><td>56</td></tr> <tr><td>6</td><td>34</td><td>129</td><td>28</td><td>107</td><td>4000</td><td>276</td><td>40</td><td>30</td></tr> <tr><td>7</td><td>34</td><td>129</td><td>28</td><td>107</td><td>4000</td><td>276</td><td>75</td><td>56</td></tr> <tr><td>8</td><td>63</td><td>239</td><td>53</td><td>199</td><td>4000</td><td>276</td><td>100</td><td>75</td></tr> <tr><td>9</td><td>63</td><td>239</td><td>53</td><td>199</td><td>5000</td><td>345</td><td>150</td><td>112</td></tr> <tr><td>A</td><td>63</td><td>239</td><td>53</td><td>199</td><td>4000</td><td>276</td><td>150</td><td>112</td></tr> <tr><td>L</td><td>63</td><td>239</td><td>53</td><td>199</td><td>5000</td><td>345</td><td>150</td><td>112</td></tr> <tr><td>Z</td><td>0.8</td><td>2.8</td><td>0.8</td><td>2.8</td><td>1500</td><td>103</td><td>0.8</td><td>0.6</td></tr> </tbody> </table>								char	60 Hz		50 Hz		psi	bar	hp	kW	gpm	lpm	gpm	lpm	0	6	23	5	19	1800	124	3	2.2	1	6	23	5	19	3000	207	5	3.7	2	10	38	8	32	3000	207	15	11	3	11	42	9	35	5000	345	25	19	4	15	57	13	47	3500	241	25	19	J	20	76	17	63	4000	276	30	22	5	25	95	21	79	5000	345	75	56	6	34	129	28	107	4000	276	40	30	7	34	129	28	107	4000	276	75	56	8	63	239	53	199	4000	276	100	75	9	63	239	53	199	5000	345	150	112	A	63	239	53	199	4000	276	150	112	L	63	239	53	199	5000	345	150	112	Z	0.8	2.8	0.8	2.8	1500	103	0.8	0.6	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>char</th> <th>color</th> </tr> <tr> <td>0</td> <td>desert sand</td> </tr> <tr> <td>1</td> <td>Tronair blue (standard)</td> </tr> <tr> <td>2</td> <td>safety yellow</td> </tr> <tr> <td>3</td> <td>red</td> </tr> <tr> <td>4</td> <td>jade green</td> </tr> <tr> <td>5</td> <td>snow white</td> </tr> <tr> <td>7</td> <td>gray</td> </tr> <tr> <td>9</td> <td>olive drab</td> </tr> <tr> <td>C</td> <td>olive drab (low IR)</td> </tr> <tr> <td>S</td> <td>special (call Tronair)</td> </tr> </table>								char	color	0	desert sand	1	Tronair blue (standard)	2	safety yellow	3	red	4	jade green	5	snow white	7	gray	9	olive drab	C	olive drab (low IR)	S	special (call Tronair)																					
char	60 Hz		50 Hz		psi	bar	hp		kW																																																																																																																																																																																												
	gpm	lpm	gpm	lpm																																																																																																																																																																																																	
0	6	23	5	19	1800	124	3	2.2																																																																																																																																																																																													
1	6	23	5	19	3000	207	5	3.7																																																																																																																																																																																													
2	10	38	8	32	3000	207	15	11																																																																																																																																																																																													
3	11	42	9	35	5000	345	25	19																																																																																																																																																																																													
4	15	57	13	47	3500	241	25	19																																																																																																																																																																																													
J	20	76	17	63	4000	276	30	22																																																																																																																																																																																													
5	25	95	21	79	5000	345	75	56																																																																																																																																																																																													
6	34	129	28	107	4000	276	40	30																																																																																																																																																																																													
7	34	129	28	107	4000	276	75	56																																																																																																																																																																																													
8	63	239	53	199	4000	276	100	75																																																																																																																																																																																													
9	63	239	53	199	5000	345	150	112																																																																																																																																																																																													
A	63	239	53	199	4000	276	150	112																																																																																																																																																																																													
L	63	239	53	199	5000	345	150	112																																																																																																																																																																																													
Z	0.8	2.8	0.8	2.8	1500	103	0.8	0.6																																																																																																																																																																																													
char	color																																																																																																																																																																																																				
0	desert sand																																																																																																																																																																																																				
1	Tronair blue (standard)																																																																																																																																																																																																				
2	safety yellow																																																																																																																																																																																																				
3	red																																																																																																																																																																																																				
4	jade green																																																																																																																																																																																																				
5	snow white																																																																																																																																																																																																				
7	gray																																																																																																																																																																																																				
9	olive drab																																																																																																																																																																																																				
C	olive drab (low IR)																																																																																																																																																																																																				
S	special (call Tronair)																																																																																																																																																																																																				
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>char</th> <th>description</th> </tr> <tr> <td>B</td> <td>Citation pkg A</td> </tr> <tr> <td>D</td> <td>JPATS</td> </tr> <tr> <td>E</td> <td>Pilatus</td> </tr> <tr> <td>F</td> <td>Citation pkg B</td> </tr> <tr> <td>G</td> <td>Gulfstream (factory)</td> </tr> <tr> <td>H</td> <td>Dash 8-100/300 only</td> </tr> <tr> <td>K</td> <td>Gulfstream (G100/200)</td> </tr> <tr> <td>R</td> <td>Agusta (AB139, factory)</td> </tr> </table>								char	description	B	Citation pkg A	D	JPATS	E	Pilatus	F	Citation pkg B	G	Gulfstream (factory)	H	Dash 8-100/300 only	K	Gulfstream (G100/200)	R	Agusta (AB139, factory)	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="10">FULL LOAD AMPS</th> </tr> <tr> <th colspan="5">supply voltage: 60 hz - 3 phase</th> <th colspan="5">supply voltage: 50 hz - 3 phase</th> </tr> <tr> <th>HP</th> <th>208 VAC</th> <th>230 VAC</th> <th>380 VAC</th> <th>460 VAC</th> <th>575 VAC</th> <th>HP</th> <th>200 VAC</th> <th>220 VAC</th> <th>380 VAC</th> <th>415 VAC</th> <th>440 VAC</th> </tr> <tr> <td>3</td> <td>9.2</td> <td>8.4</td> <td>4.8</td> <td>4.2</td> <td>3.7</td> <td>3</td> <td>8.4</td> <td>9.3</td> <td>4.6</td> <td>4.6</td> <td>4.6</td> </tr> <tr> <td>5</td> <td>15</td> <td>13.6</td> <td>7.8</td> <td>6.8</td> <td>5.4</td> <td>5</td> <td>13.0</td> <td>15.0</td> <td>7.5</td> <td>7.5</td> <td>7.5</td> </tr> <tr> <td>10</td> <td>28.8</td> <td>26.0</td> <td>15.7</td> <td>13.0</td> <td>10.4</td> <td>10</td> <td>26.0</td> <td>26.0</td> <td>13.0</td> <td>13.0</td> <td>13.0</td> </tr> <tr> <td>15</td> <td>44.2</td> <td>40.0</td> <td>24.2</td> <td>20.0</td> <td>16.0</td> <td>15</td> <td>48.0</td> <td>41.0</td> <td>23.7</td> <td>23.0</td> <td>22.0</td> </tr> <tr> <td>20</td> <td>59.3</td> <td>53.6</td> <td>31.8</td> <td>26.8</td> <td>21.4</td> <td>20</td> <td>61.6</td> <td>51.9</td> <td>30.0</td> <td>29.1</td> <td>28.1</td> </tr> <tr> <td>25</td> <td>73.0</td> <td>66.0</td> <td>38.0</td> <td>33.0</td> <td>26.4</td> <td>25</td> <td>75.0</td> <td>72.0</td> <td>36.0</td> <td>36.0</td> <td>35.0</td> </tr> <tr> <td>30</td> <td>86.3</td> <td>78.0</td> <td>42.5</td> <td>39.0</td> <td>31.2</td> <td>30</td> <td>89.0</td> <td>78.0</td> <td>45.0</td> <td>43.0</td> <td>39.0</td> </tr> <tr> <td>40</td> <td>117.2</td> <td>106.0</td> <td>57.0</td> <td>53.0</td> <td>42.0</td> <td>40</td> <td>120.5</td> <td>103.0</td> <td>62.0</td> <td>60.0</td> <td>56.0</td> </tr> <tr> <td>75</td> <td>N/A</td> <td>N/A</td> <td>103.8</td> <td>92.0</td> <td>73.6</td> <td>75</td> <td>N/A</td> <td>N/A</td> <td>107.0</td> <td>105.0</td> <td>92.0</td> </tr> <tr> <td>100</td> <td>N/A</td> <td>N/A</td> <td>130.0</td> <td>121.0</td> <td>96.8</td> <td>100</td> <td>N/A</td> <td>N/A</td> <td>146.0</td> <td>134.0</td> <td>124.0</td> </tr> <tr> <td>150</td> <td>N/A</td> <td>N/A</td> <td>192.0</td> <td>171.0</td> <td>137.0</td> <td>150</td> <td>N/A</td> <td>N/A</td> <td>208.0</td> <td>190.0</td> <td>179.0</td> </tr> </table>								FULL LOAD AMPS										supply voltage: 60 hz - 3 phase					supply voltage: 50 hz - 3 phase					HP	208 VAC	230 VAC	380 VAC	460 VAC	575 VAC	HP	200 VAC	220 VAC	380 VAC	415 VAC	440 VAC	3	9.2	8.4	4.8	4.2	3.7	3	8.4	9.3	4.6	4.6	4.6	5	15	13.6	7.8	6.8	5.4	5	13.0	15.0	7.5	7.5	7.5	10	28.8	26.0	15.7	13.0	10.4	10	26.0	26.0	13.0	13.0	13.0	15	44.2	40.0	24.2	20.0	16.0	15	48.0	41.0	23.7	23.0	22.0	20	59.3	53.6	31.8	26.8	21.4	20	61.6	51.9	30.0	29.1	28.1	25	73.0	66.0	38.0	33.0	26.4	25	75.0	72.0	36.0	36.0	35.0	30	86.3	78.0	42.5	39.0	31.2	30	89.0	78.0	45.0	43.0	39.0	40	117.2	106.0	57.0	53.0	42.0	40	120.5	103.0	62.0	60.0	56.0	75	N/A	N/A	103.8	92.0	73.6	75	N/A	N/A	107.0	105.0	92.0	100	N/A	N/A	130.0	121.0	96.8	100	N/A	N/A	146.0	134.0	124.0	150	N/A	N/A	192.0	171.0	137.0	150	N/A	N/A	208.0	190.0	179.0
char	description																																																																																																																																																																																																				
B	Citation pkg A																																																																																																																																																																																																				
D	JPATS																																																																																																																																																																																																				
E	Pilatus																																																																																																																																																																																																				
F	Citation pkg B																																																																																																																																																																																																				
G	Gulfstream (factory)																																																																																																																																																																																																				
H	Dash 8-100/300 only																																																																																																																																																																																																				
K	Gulfstream (G100/200)																																																																																																																																																																																																				
R	Agusta (AB139, factory)																																																																																																																																																																																																				
FULL LOAD AMPS																																																																																																																																																																																																					
supply voltage: 60 hz - 3 phase					supply voltage: 50 hz - 3 phase																																																																																																																																																																																																
HP	208 VAC	230 VAC	380 VAC	460 VAC	575 VAC	HP	200 VAC	220 VAC	380 VAC	415 VAC	440 VAC																																																																																																																																																																																										
3	9.2	8.4	4.8	4.2	3.7	3	8.4	9.3	4.6	4.6	4.6																																																																																																																																																																																										
5	15	13.6	7.8	6.8	5.4	5	13.0	15.0	7.5	7.5	7.5																																																																																																																																																																																										
10	28.8	26.0	15.7	13.0	10.4	10	26.0	26.0	13.0	13.0	13.0																																																																																																																																																																																										
15	44.2	40.0	24.2	20.0	16.0	15	48.0	41.0	23.7	23.0	22.0																																																																																																																																																																																										
20	59.3	53.6	31.8	26.8	21.4	20	61.6	51.9	30.0	29.1	28.1																																																																																																																																																																																										
25	73.0	66.0	38.0	33.0	26.4	25	75.0	72.0	36.0	36.0	35.0																																																																																																																																																																																										
30	86.3	78.0	42.5	39.0	31.2	30	89.0	78.0	45.0	43.0	39.0																																																																																																																																																																																										
40	117.2	106.0	57.0	53.0	42.0	40	120.5	103.0	62.0	60.0	56.0																																																																																																																																																																																										
75	N/A	N/A	103.8	92.0	73.6	75	N/A	N/A	107.0	105.0	92.0																																																																																																																																																																																										
100	N/A	N/A	130.0	121.0	96.8	100	N/A	N/A	146.0	134.0	124.0																																																																																																																																																																																										
150	N/A	N/A	192.0	171.0	137.0	150	N/A	N/A	208.0	190.0	179.0																																																																																																																																																																																										