

Hydraulic Power Units - Ordering Instructions

- Step 1** – Determine the size of the Hydraulic Power Unit required. Check the aircraft maintenance manual, or refer to Tronair's Aircraft Tool and Equipment list at tronair.com
- Step 2** – Select the correct fluid type that matches your aircraft
- Step 3** – Determine if the unit requires a CE mark and/or an Electric Soft Start (call for soft start availability)
- Step 4** – Choose a paint color from the available colors
- Step 5** – Select quick disconnect couplings to attach the hoses to the aircraft bulkhead fittings. These couplings will become part of the model number sequence, they are attached to hose ends upon receipt (pgs 94 - 98)
- Step 6** – Determine the input voltage the Hydraulic Power Unit will be operating at. **When ordering, the most common error is selecting incorrect input voltages** (To check input voltage, measure from L1 to L2, L1 to L3, and L2 to L3. The highest voltage obtained from these readings is the correct input voltage)
- Step 7** – Select additional features to customize your unit. We offer a broad range of options to enhance your Hydraulic Power Unit to your particular needs or budget. Options listed in the chart must be in alphabetical order. Refer to the option matrix (below) for standard features per model number

MANDATORY INFORMATION							OPTIONS (alphabetical order)																																																																																																																																																																																																																																																										
5																																																																																																																																																																																																																																																																	
<table border="1"> <tr> <th>char</th> <th>build</th> </tr> <tr> <td>0</td> <td>Standard</td> </tr> <tr> <td>1</td> <td>CE Compliant</td> </tr> <tr> <td>2</td> <td>Standard Soft Start</td> </tr> <tr> <td>3</td> <td>CE Soft Start</td> </tr> </table>							char	build	0	Standard	1	CE Compliant	2	Standard Soft Start	3	CE Soft Start	<table border="1"> <tr> <th>char</th> <th>fluid</th> </tr> <tr> <td>1</td> <td>MIL-PRF-5606</td> </tr> <tr> <td>2</td> <td>MIL-PRF-83282</td> </tr> <tr> <td>3</td> <td>Phosphate Ester (Skydrol, Hyjet)</td> </tr> <tr> <td>4</td> <td>MIL-PRF-87257</td> </tr> </table>							char	fluid	1	MIL-PRF-5606	2	MIL-PRF-83282	3	Phosphate Ester (Skydrol, Hyjet)	4	MIL-PRF-87257	<table border="1"> <tr> <th>char</th> <th>volt/freq/phase</th> <th>input cord</th> </tr> <tr> <td>0</td> <td>208V/60HZ/3PH</td> <td rowspan="9">50 ft (15.2 m) input cord length</td> </tr> <tr> <td>1</td> <td>230V/60HZ/3PH</td> </tr> <tr> <td>2</td> <td>380V/60HZ/3PH</td> </tr> <tr> <td>3</td> <td>460V/60HZ/3PH</td> </tr> <tr> <td>4</td> <td>575V/60HZ/3PH *</td> </tr> <tr> <td>5</td> <td>200V/50HZ/3PH</td> </tr> <tr> <td>6</td> <td>220V/50HZ/3PH</td> </tr> <tr> <td>7</td> <td>380V/50HZ/3PH</td> </tr> <tr> <td>8</td> <td>415V/50HZ/3PH</td> </tr> <tr> <td>9</td> <td>440V/50HZ/3PH</td> </tr> <tr> <td>Q</td> <td>208V/60HZ/3PH</td> <td rowspan="9">100 ft (30.5 m) input cord length</td> </tr> <tr> <td>R</td> <td>230V/60HZ/3PH</td> </tr> <tr> <td>S</td> <td>380V/60HZ/3PH</td> </tr> <tr> <td>T</td> <td>460V/60HZ/3PH</td> </tr> <tr> <td>U</td> <td>575V/60HZ/3PH *</td> </tr> <tr> <td>V</td> <td>200V/50HZ/3PH</td> </tr> <tr> <td>W</td> <td>220V/50HZ/3PH</td> </tr> <tr> <td>X</td> <td>380V/50HZ/3PH</td> </tr> <tr> <td>Y</td> <td>415V/50HZ/3PH</td> </tr> <tr> <td>Z</td> <td>440V/50HZ/3PH</td> </tr> <tr> <td>E</td> <td>220V/50-60HZ/1P</td> <td>15 ft</td> </tr> <tr> <td>F</td> <td>120V/60HZ/1PH</td> <td>(4.6 m)</td> </tr> </table>							char	volt/freq/phase	input cord	0	208V/60HZ/3PH	50 ft (15.2 m) input cord length	1	230V/60HZ/3PH	2	380V/60HZ/3PH	3	460V/60HZ/3PH	4	575V/60HZ/3PH *	5	200V/50HZ/3PH	6	220V/50HZ/3PH	7	380V/50HZ/3PH	8	415V/50HZ/3PH	9	440V/50HZ/3PH	Q	208V/60HZ/3PH	100 ft (30.5 m) input cord length	R	230V/60HZ/3PH	S	380V/60HZ/3PH	T	460V/60HZ/3PH	U	575V/60HZ/3PH *	V	200V/50HZ/3PH	W	220V/50HZ/3PH	X	380V/50HZ/3PH	Y	415V/50HZ/3PH	Z	440V/50HZ/3PH	E	220V/50-60HZ/1P	15 ft	F	120V/60HZ/1PH	(4.6 m)	<table border="1"> <tr> <th>char</th> <th>description</th> </tr> <tr> <td>A</td> <td>25 ft hoses</td> </tr> <tr> <td>B</td> <td>50 ft hoses</td> </tr> <tr> <td>AA</td> <td>25 ft hoses (dual system)</td> </tr> <tr> <td>AB</td> <td>25 ft hoses and 50 ft hoses</td> </tr> <tr> <td>BB</td> <td>50 ft hoses (dual system)</td> </tr> <tr> <td>C</td> <td>dual system</td> </tr> <tr> <td>D</td> <td>dual system w/crossover check</td> </tr> <tr> <td>E</td> <td>hourmeter (50HZ)</td> </tr> <tr> <td>F</td> <td>hourmeter (60HZ)</td> </tr> <tr> <td>G</td> <td>voltage monitor (200-230V)</td> </tr> <tr> <td>H</td> <td>voltage monitor (380V)</td> </tr> <tr> <td>I</td> <td>voltage monitor (415-460V)</td> </tr> <tr> <td>J</td> <td>voltage monitor (575V)</td> </tr> <tr> <td>K</td> <td>pyrometer</td> </tr> <tr> <td>L</td> <td>electric reservoir level</td> </tr> <tr> <td>M</td> <td>hand pump</td> </tr> <tr> <td>N</td> <td>towing/trailer package</td> </tr> <tr> <td>P</td> <td>reservoir return</td> </tr> <tr> <td>Q</td> <td>calibration port</td> </tr> <tr> <td>R</td> <td>electric filter clogged indicator</td> </tr> <tr> <td>S</td> <td>electric over temperature</td> </tr> <tr> <td>T</td> <td>return back pressure w/sight gauge</td> </tr> <tr> <td>U</td> <td>return sight gauge</td> </tr> <tr> <td>V</td> <td>return back pressure</td> </tr> <tr> <td>W</td> <td>return filter</td> </tr> <tr> <td>X</td> <td>height extension cart</td> </tr> <tr> <td>Y</td> <td>return sight gauge (dual system)</td> </tr> <tr> <td>Z</td> <td>no return valves (dual system)</td> </tr> <tr> <td>1</td> <td>return back pressure (dual system)</td> </tr> <tr> <td>2</td> <td>red stack light</td> </tr> <tr> <td>3</td> <td>triple system</td> </tr> <tr> <td>4</td> <td>drip pan</td> </tr> <tr> <td>5</td> <td>remote e-stop (50 ft)</td> </tr> <tr> <td>6</td> <td>return sight gauge (triple system)</td> </tr> <tr> <td>7</td> <td>hand pump (large displacement)</td> </tr> <tr> <td>8</td> <td>pressure reducing valve (single)</td> </tr> </table>							char	description	A	25 ft hoses	B	50 ft hoses	AA	25 ft hoses (dual system)	AB	25 ft hoses and 50 ft hoses	BB	50 ft hoses (dual system)	C	dual system	D	dual system w/crossover check	E	hourmeter (50HZ)	F	hourmeter (60HZ)	G	voltage monitor (200-230V)	H	voltage monitor (380V)	I	voltage monitor (415-460V)	J	voltage monitor (575V)	K	pyrometer	L	electric reservoir level	M	hand pump	N	towing/trailer package	P	reservoir return	Q	calibration port	R	electric filter clogged indicator	S	electric over temperature	T	return back pressure w/sight gauge	U	return sight gauge	V	return back pressure	W	return filter	X	height extension cart	Y	return sight gauge (dual system)	Z	no return valves (dual system)	1	return back pressure (dual system)	2	red stack light	3	triple system	4	drip pan	5	remote e-stop (50 ft)	6	return sight gauge (triple system)	7	hand pump (large displacement)	8	pressure reducing valve (single)																																																																																					
							char	build																																																																																																																																																																																																																																																									
0	Standard																																																																																																																																																																																																																																																																
1	CE Compliant																																																																																																																																																																																																																																																																
2	Standard Soft Start																																																																																																																																																																																																																																																																
3	CE Soft Start																																																																																																																																																																																																																																																																
char	fluid																																																																																																																																																																																																																																																																
1	MIL-PRF-5606																																																																																																																																																																																																																																																																
2	MIL-PRF-83282																																																																																																																																																																																																																																																																
3	Phosphate Ester (Skydrol, Hyjet)																																																																																																																																																																																																																																																																
4	MIL-PRF-87257																																																																																																																																																																																																																																																																
char	volt/freq/phase	input cord																																																																																																																																																																																																																																																															
0	208V/60HZ/3PH	50 ft (15.2 m) input cord length																																																																																																																																																																																																																																																															
1	230V/60HZ/3PH																																																																																																																																																																																																																																																																
2	380V/60HZ/3PH																																																																																																																																																																																																																																																																
3	460V/60HZ/3PH																																																																																																																																																																																																																																																																
4	575V/60HZ/3PH *																																																																																																																																																																																																																																																																
5	200V/50HZ/3PH																																																																																																																																																																																																																																																																
6	220V/50HZ/3PH																																																																																																																																																																																																																																																																
7	380V/50HZ/3PH																																																																																																																																																																																																																																																																
8	415V/50HZ/3PH																																																																																																																																																																																																																																																																
9	440V/50HZ/3PH																																																																																																																																																																																																																																																																
Q	208V/60HZ/3PH	100 ft (30.5 m) input cord length																																																																																																																																																																																																																																																															
R	230V/60HZ/3PH																																																																																																																																																																																																																																																																
S	380V/60HZ/3PH																																																																																																																																																																																																																																																																
T	460V/60HZ/3PH																																																																																																																																																																																																																																																																
U	575V/60HZ/3PH *																																																																																																																																																																																																																																																																
V	200V/50HZ/3PH																																																																																																																																																																																																																																																																
W	220V/50HZ/3PH																																																																																																																																																																																																																																																																
X	380V/50HZ/3PH																																																																																																																																																																																																																																																																
Y	415V/50HZ/3PH																																																																																																																																																																																																																																																																
Z	440V/50HZ/3PH																																																																																																																																																																																																																																																																
E	220V/50-60HZ/1P	15 ft																																																																																																																																																																																																																																																															
F	120V/60HZ/1PH	(4.6 m)																																																																																																																																																																																																																																																															
char	description																																																																																																																																																																																																																																																																
A	25 ft hoses																																																																																																																																																																																																																																																																
B	50 ft hoses																																																																																																																																																																																																																																																																
AA	25 ft hoses (dual system)																																																																																																																																																																																																																																																																
AB	25 ft hoses and 50 ft hoses																																																																																																																																																																																																																																																																
BB	50 ft hoses (dual system)																																																																																																																																																																																																																																																																
C	dual system																																																																																																																																																																																																																																																																
D	dual system w/crossover check																																																																																																																																																																																																																																																																
E	hourmeter (50HZ)																																																																																																																																																																																																																																																																
F	hourmeter (60HZ)																																																																																																																																																																																																																																																																
G	voltage monitor (200-230V)																																																																																																																																																																																																																																																																
H	voltage monitor (380V)																																																																																																																																																																																																																																																																
I	voltage monitor (415-460V)																																																																																																																																																																																																																																																																
J	voltage monitor (575V)																																																																																																																																																																																																																																																																
K	pyrometer																																																																																																																																																																																																																																																																
L	electric reservoir level																																																																																																																																																																																																																																																																
M	hand pump																																																																																																																																																																																																																																																																
N	towing/trailer package																																																																																																																																																																																																																																																																
P	reservoir return																																																																																																																																																																																																																																																																
Q	calibration port																																																																																																																																																																																																																																																																
R	electric filter clogged indicator																																																																																																																																																																																																																																																																
S	electric over temperature																																																																																																																																																																																																																																																																
T	return back pressure w/sight gauge																																																																																																																																																																																																																																																																
U	return sight gauge																																																																																																																																																																																																																																																																
V	return back pressure																																																																																																																																																																																																																																																																
W	return filter																																																																																																																																																																																																																																																																
X	height extension cart																																																																																																																																																																																																																																																																
Y	return sight gauge (dual system)																																																																																																																																																																																																																																																																
Z	no return valves (dual system)																																																																																																																																																																																																																																																																
1	return back pressure (dual system)																																																																																																																																																																																																																																																																
2	red stack light																																																																																																																																																																																																																																																																
3	triple system																																																																																																																																																																																																																																																																
4	drip pan																																																																																																																																																																																																																																																																
5	remote e-stop (50 ft)																																																																																																																																																																																																																																																																
6	return sight gauge (triple system)																																																																																																																																																																																																																																																																
7	hand pump (large displacement)																																																																																																																																																																																																																																																																
8	pressure reducing valve (single)																																																																																																																																																																																																																																																																
<table border="1"> <tr> <th>char</th> <th>gpm</th> <th>lpm</th> <th>psi</th> <th>bar</th> <th>hp</th> <th>kW</th> <th>FR</th> </tr> <tr> <td>0</td> <td>6</td> <td>22.7</td> <td>1800</td> <td>124</td> <td>3</td> <td>2.24</td> <td></td> </tr> <tr> <td>1</td> <td>6</td> <td>22.7</td> <td>3000</td> <td>207</td> <td>5</td> <td>3.73</td> <td></td> </tr> <tr> <td>2</td> <td>10</td> <td>37.9</td> <td>3000</td> <td>207</td> <td>15</td> <td>11.2</td> <td></td> </tr> <tr> <td>3</td> <td>11</td> <td>41.6</td> <td>5000</td> <td>345</td> <td>25</td> <td>18.6</td> <td>B</td> </tr> <tr> <td>4</td> <td>15</td> <td>56.8</td> <td>3500</td> <td>241</td> <td>25</td> <td>18.6</td> <td></td> </tr> <tr> <td>J</td> <td>20</td> <td>75.7</td> <td>4000</td> <td>276</td> <td>30</td> <td>22.4</td> <td></td> </tr> <tr> <td>5</td> <td>25</td> <td>94.6</td> <td>5000</td> <td>345</td> <td>75</td> <td>55.9</td> <td></td> </tr> <tr> <td>6</td> <td>34</td> <td>129</td> <td>3500</td> <td>241</td> <td>40</td> <td>29.8</td> <td>C</td> </tr> <tr> <td>7</td> <td>34</td> <td>129</td> <td>3500</td> <td>241</td> <td>75</td> <td>55.9</td> <td></td> </tr> <tr> <td>8</td> <td>50</td> <td>189</td> <td>3500</td> <td>241</td> <td>100</td> <td>74.6</td> <td></td> </tr> <tr> <td>9</td> <td>50</td> <td>189</td> <td>5000</td> <td>345</td> <td>150</td> <td>112</td> <td></td> </tr> <tr> <td>A</td> <td>65</td> <td>246</td> <td>3500</td> <td>241</td> <td>150</td> <td>112</td> <td>D</td> </tr> <tr> <td>L</td> <td>65</td> <td>246</td> <td>5000</td> <td>345</td> <td>150</td> <td>112</td> <td></td> </tr> <tr> <td>B</td> <td colspan="4">Citation pkg A</td> <td>5</td> <td>3.73</td> <td></td> </tr> <tr> <td>C</td> <td colspan="4">Lear pkg (Lear 45)</td> <td>20</td> <td>14.9</td> <td></td> </tr> <tr> <td>D</td> <td colspan="4">JPATS</td> <td>10</td> <td>7.46</td> <td></td> </tr> <tr> <td>E</td> <td colspan="4">Pilatus</td> <td>10</td> <td>7.46</td> <td></td> </tr> <tr> <td>F</td> <td colspan="4">Citation pkg B</td> <td>3</td> <td>2.24</td> <td></td> </tr> <tr> <td>G</td> <td colspan="4">Gulfstream (factory)</td> <td>40</td> <td>29.8</td> <td>C</td> </tr> <tr> <td>H</td> <td colspan="4">Dash 8-100/300 only</td> <td>15</td> <td>11.2</td> <td>B</td> </tr> <tr> <td>K</td> <td colspan="4">Gulfstream (G100/200)</td> <td>25</td> <td>18.6</td> <td>B</td> </tr> <tr> <td>P</td> <td colspan="4">Falcon 7X</td> <td>30</td> <td>22.4</td> <td>B</td> </tr> <tr> <td>Q</td> <td colspan="4">Falcon 7X (factory)</td> <td>40</td> <td>29.8</td> <td>C</td> </tr> <tr> <td>R</td> <td colspan="4">Agusta (AB139, factory)</td> <td>30</td> <td>22.4</td> <td>B</td> </tr> </table>							char	gpm	lpm	psi	bar	hp	kW	FR	0	6	22.7	1800	124	3	2.24		1	6	22.7	3000	207	5	3.73		2	10	37.9	3000	207	15	11.2		3	11	41.6	5000	345	25	18.6	B	4	15	56.8	3500	241	25	18.6		J	20	75.7	4000	276	30	22.4		5	25	94.6	5000	345	75	55.9		6	34	129	3500	241	40	29.8	C	7	34	129	3500	241	75	55.9		8	50	189	3500	241	100	74.6		9	50	189	5000	345	150	112		A	65	246	3500	241	150	112	D	L	65	246	5000	345	150	112		B	Citation pkg A				5	3.73		C	Lear pkg (Lear 45)				20	14.9		D	JPATS				10	7.46		E	Pilatus				10	7.46		F	Citation pkg B				3	2.24		G	Gulfstream (factory)				40	29.8	C	H	Dash 8-100/300 only				15	11.2	B	K	Gulfstream (G100/200)				25	18.6	B	P	Falcon 7X				30	22.4	B	Q	Falcon 7X (factory)				40	29.8	C	R	Agusta (AB139, factory)				30	22.4	B	<table border="1"> <tr> <th>char</th> <th>color</th> </tr> <tr> <td>0</td> <td>desert sand</td> </tr> <tr> <td>1</td> <td>Tronair blue (standard)</td> </tr> <tr> <td>2</td> <td>safety yellow</td> </tr> <tr> <td>3</td> <td>red</td> </tr> <tr> <td>4</td> <td>jade green</td> </tr> <tr> <td>5</td> <td>snow white</td> </tr> <tr> <td>7</td> <td>gray</td> </tr> <tr> <td>9</td> <td>olive drab</td> </tr> <tr> <td>C</td> <td>olive drab (low IR) *</td> <td>* additional cost</td> </tr> <tr> <td>S</td> <td>special (call Tronair) *</td> <td>* additional cost</td> </tr> </table>							char	color	0	desert sand	1	Tronair blue (standard)	2	safety yellow	3	red	4	jade green	5	snow white	7	gray	9	olive drab	C	olive drab (low IR) *	* additional cost	S	special (call Tronair) *	* additional cost																				
char	gpm	lpm	psi	bar	hp	kW	FR																																																																																																																																																																																																																																																										
0	6	22.7	1800	124	3	2.24																																																																																																																																																																																																																																																											
1	6	22.7	3000	207	5	3.73																																																																																																																																																																																																																																																											
2	10	37.9	3000	207	15	11.2																																																																																																																																																																																																																																																											
3	11	41.6	5000	345	25	18.6	B																																																																																																																																																																																																																																																										
4	15	56.8	3500	241	25	18.6																																																																																																																																																																																																																																																											
J	20	75.7	4000	276	30	22.4																																																																																																																																																																																																																																																											
5	25	94.6	5000	345	75	55.9																																																																																																																																																																																																																																																											
6	34	129	3500	241	40	29.8	C																																																																																																																																																																																																																																																										
7	34	129	3500	241	75	55.9																																																																																																																																																																																																																																																											
8	50	189	3500	241	100	74.6																																																																																																																																																																																																																																																											
9	50	189	5000	345	150	112																																																																																																																																																																																																																																																											
A	65	246	3500	241	150	112	D																																																																																																																																																																																																																																																										
L	65	246	5000	345	150	112																																																																																																																																																																																																																																																											
B	Citation pkg A				5	3.73																																																																																																																																																																																																																																																											
C	Lear pkg (Lear 45)				20	14.9																																																																																																																																																																																																																																																											
D	JPATS				10	7.46																																																																																																																																																																																																																																																											
E	Pilatus				10	7.46																																																																																																																																																																																																																																																											
F	Citation pkg B				3	2.24																																																																																																																																																																																																																																																											
G	Gulfstream (factory)				40	29.8	C																																																																																																																																																																																																																																																										
H	Dash 8-100/300 only				15	11.2	B																																																																																																																																																																																																																																																										
K	Gulfstream (G100/200)				25	18.6	B																																																																																																																																																																																																																																																										
P	Falcon 7X				30	22.4	B																																																																																																																																																																																																																																																										
Q	Falcon 7X (factory)				40	29.8	C																																																																																																																																																																																																																																																										
R	Agusta (AB139, factory)				30	22.4	B																																																																																																																																																																																																																																																										
char	color																																																																																																																																																																																																																																																																
0	desert sand																																																																																																																																																																																																																																																																
1	Tronair blue (standard)																																																																																																																																																																																																																																																																
2	safety yellow																																																																																																																																																																																																																																																																
3	red																																																																																																																																																																																																																																																																
4	jade green																																																																																																																																																																																																																																																																
5	snow white																																																																																																																																																																																																																																																																
7	gray																																																																																																																																																																																																																																																																
9	olive drab																																																																																																																																																																																																																																																																
C	olive drab (low IR) *	* additional cost																																																																																																																																																																																																																																																															
S	special (call Tronair) *	* additional cost																																																																																																																																																																																																																																																															
<table border="1"> <tr> <th colspan="14">FULL LOAD AMPS</th> </tr> <tr> <th colspan="7">supply voltage: 60 hz - 3 phase</th> <th colspan="7">supply voltage: 50 hz - 3 phase</th> </tr> <tr> <th>HP</th> <th>208 VAC</th> <th>230 VAC</th> <th>380 VAC</th> <th>460 VAC</th> <th>575 VAC</th> <th>HP</th> <th>200 VAC</th> <th>220 VAC</th> <th>380 VAC</th> <th>415 VAC</th> <th>440 VAC</th> <th>HP</th> <th>200 VAC</th> <th>220 VAC</th> <th>380 VAC</th> <th>415 VAC</th> <th>440 VAC</th> </tr> <tr> <td>3</td> <td>9.3</td> <td>8.4</td> <td>4.8</td> <td>4.2</td> <td>3.4</td> <td>3</td> <td>8.4</td> <td>8.4</td> <td>4.2</td> <td>4.2</td> <td>4.2</td> <td>3</td> <td>8.4</td> <td>8.4</td> <td>4.2</td> <td>4.2</td> <td>4.2</td> </tr> <tr> <td>5</td> <td>14.4</td> <td>13.0</td> <td>7.8</td> <td>6.5</td> <td>5.2</td> <td>5</td> <td>13.0</td> <td>13.0</td> <td>6.5</td> <td>6.5</td> <td>6.5</td> <td>5</td> <td>13.0</td> <td>13.0</td> <td>6.5</td> <td>6.5</td> <td>6.5</td> </tr> <tr> <td>10</td> <td>29.0</td> <td>26.0</td> <td>15.8</td> <td>13.0</td> <td>10.4</td> <td>10</td> <td>26.0</td> <td>26.0</td> <td>13.0</td> <td>13.0</td> <td>13.0</td> <td>10</td> <td>26.0</td> <td>26.0</td> <td>13.0</td> <td>13.0</td> <td>13.0</td> </tr> <tr> <td>15</td> <td>44.2</td> <td>40.0</td> <td>24.2</td> <td>20.0</td> <td>16.0</td> <td>15</td> <td>48.0</td> <td>41.0</td> <td>23.7</td> <td>23.0</td> <td>22.0</td> <td>15</td> <td>48.0</td> <td>41.0</td> <td>23.7</td> <td>23.0</td> <td>22.0</td> </tr> <tr> <td>20</td> <td>59.3</td> <td>53.6</td> <td>31.8</td> <td>26.8</td> <td>21.4</td> <td>20</td> <td>61.6</td> <td>51.9</td> <td>30.0</td> <td>29.1</td> <td>28.1</td> <td>20</td> <td>61.6</td> <td>51.9</td> <td>30.0</td> <td>29.1</td> <td>28.1</td> </tr> <tr> <td>25</td> <td>73.0</td> <td>66.0</td> <td>38.0</td> <td>33.0</td> <td>26.4</td> <td>25</td> <td>75.0</td> <td>72.0</td> <td>36.0</td> <td>36.0</td> <td>35.0</td> <td>25</td> <td>75.0</td> <td>72.0</td> <td>36.0</td> <td>36.0</td> <td>35.0</td> </tr> <tr> <td>30</td> <td>86.3</td> <td>78.0</td> <td>42.5</td> <td>39.0</td> <td>31.2</td> <td>30</td> <td>89.0</td> <td>78.0</td> <td>45.0</td> <td>43.0</td> <td>39.0</td> <td>30</td> <td>89.0</td> <td>78.0</td> <td>45.0</td> <td>43.0</td> <td>39.0</td> </tr> <tr> <td>40</td> <td>117.2</td> <td>106.0</td> <td>57.0</td> <td>53.0</td> <td>42.0</td> <td>40</td> <td>120.5</td> <td>103.0</td> <td>62.0</td> <td>60.0</td> <td>56.0</td> <td>40</td> <td>120.5</td> <td>103.0</td> <td>62.0</td> <td>60.0</td> <td>56.0</td> </tr> <tr> <td>75</td> <td>N/A</td> <td>N/A</td> <td>105.8</td> <td>92.0</td> <td>73.6</td> <td>75</td> <td>N/A</td> <td>N/A</td> <td>107.0</td> <td>105.0</td> <td>92.0</td> <td>75</td> <td>N/A</td> <td>N/A</td> <td>107.0</td> <td>105.0</td> <td>92.0</td> </tr> <tr> <td>100</td> <td>N/A</td> <td>N/A</td> <td>130.0</td> <td>121.0</td> <td>96.8</td> <td>100</td> <td>N/A</td> <td>N/A</td> <td>146.0</td> <td>134.0</td> <td>124.0</td> <td>100</td> <td>N/A</td> <td>N/A</td> <td>146.0</td> <td>134.0</td> <td>124.0</td> </tr> <tr> <td>150</td> <td>N/A</td> <td>N/A</td> <td>192.1</td> <td>171.0</td> <td>136.8</td> <td>150</td> <td>N/A</td> <td>N/A</td> <td>208.0</td> <td>190.0</td> <td>179.0</td> <td>150</td> <td>N/A</td> <td>N/A</td> <td>208.0</td> <td>190.0</td> <td>179.0</td> </tr> </table>														FULL LOAD AMPS														supply voltage: 60 hz - 3 phase							supply voltage: 50 hz - 3 phase							HP	208 VAC	230 VAC	380 VAC	460 VAC	575 VAC	HP	200 VAC	220 VAC	380 VAC	415 VAC	440 VAC	HP	200 VAC	220 VAC	380 VAC	415 VAC	440 VAC	3	9.3	8.4	4.8	4.2	3.4	3	8.4	8.4	4.2	4.2	4.2	3	8.4	8.4	4.2	4.2	4.2	5	14.4	13.0	7.8	6.5	5.2	5	13.0	13.0	6.5	6.5	6.5	5	13.0	13.0	6.5	6.5	6.5	10	29.0	26.0	15.8	13.0	10.4	10	26.0	26.0	13.0	13.0	13.0	10	26.0	26.0	13.0	13.0	13.0	15	44.2	40.0	24.2	20.0	16.0	15	48.0	41.0	23.7	23.0	22.0	15	48.0	41.0	23.7	23.0	22.0	20	59.3	53.6	31.8	26.8	21.4	20	61.6	51.9	30.0	29.1	28.1	20	61.6	51.9	30.0	29.1	28.1	25	73.0	66.0	38.0	33.0	26.4	25	75.0	72.0	36.0	36.0	35.0	25	75.0	72.0	36.0	36.0	35.0	30	86.3	78.0	42.5	39.0	31.2	30	89.0	78.0	45.0	43.0	39.0	30	89.0	78.0	45.0	43.0	39.0	40	117.2	106.0	57.0	53.0	42.0	40	120.5	103.0	62.0	60.0	56.0	40	120.5	103.0	62.0	60.0	56.0	75	N/A	N/A	105.8	92.0	73.6	75	N/A	N/A	107.0	105.0	92.0	75	N/A	N/A	107.0	105.0	92.0	100	N/A	N/A	130.0	121.0	96.8	100	N/A	N/A	146.0	134.0	124.0	100	N/A	N/A	146.0	134.0	124.0	150	N/A	N/A	192.1	171.0	136.8	150	N/A	N/A	208.0	190.0	179.0	150	N/A	N/A	208.0	190.0	179.0
FULL LOAD AMPS																																																																																																																																																																																																																																																																	
supply voltage: 60 hz - 3 phase							supply voltage: 50 hz - 3 phase																																																																																																																																																																																																																																																										
HP	208 VAC	230 VAC	380 VAC	460 VAC	575 VAC	HP	200 VAC	220 VAC	380 VAC	415 VAC	440 VAC	HP	200 VAC	220 VAC	380 VAC	415 VAC	440 VAC																																																																																																																																																																																																																																																
3	9.3	8.4	4.8	4.2	3.4	3	8.4	8.4	4.2	4.2	4.2	3	8.4	8.4	4.2	4.2	4.2																																																																																																																																																																																																																																																
5	14.4	13.0	7.8	6.5	5.2	5	13.0	13.0	6.5	6.5	6.5	5	13.0	13.0	6.5	6.5	6.5																																																																																																																																																																																																																																																
10	29.0	26.0	15.8	13.0	10.4	10	26.0	26.0	13.0	13.0	13.0	10	26.0	26.0	13.0	13.0	13.0																																																																																																																																																																																																																																																
15	44.2	40.0	24.2	20.0	16.0	15	48.0	41.0	23.7	23.0	22.0	15	48.0	41.0	23.7	23.0	22.0																																																																																																																																																																																																																																																
20	59.3	53.6	31.8	26.8	21.4	20	61.6	51.9	30.0	29.1	28.1	20	61.6	51.9	30.0	29.1	28.1																																																																																																																																																																																																																																																
25	73.0	66.0	38.0	33.0	26.4	25	75.0	72.0	36.0	36.0	35.0	25	75.0	72.0	36.0	36.0	35.0																																																																																																																																																																																																																																																
30	86.3	78.0	42.5	39.0	31.2	30	89.0	78.0	45.0	43.0	39.0	30	89.0	78.0	45.0	43.0	39.0																																																																																																																																																																																																																																																
40	117.2	106.0	57.0	53.0	42.0	40	120.5	103.0	62.0	60.0	56.0	40	120.5	103.0	62.0	60.0	56.0																																																																																																																																																																																																																																																
75	N/A	N/A	105.8	92.0	73.6	75	N/A	N/A	107.0	105.0	92.0	75	N/A	N/A	107.0	105.0	92.0																																																																																																																																																																																																																																																
100	N/A	N/A	130.0	121.0	96.8	100	N/A	N/A	146.0	134.0	124.0	100	N/A	N/A	146.0	134.0	124.0																																																																																																																																																																																																																																																
150	N/A	N/A	192.1	171.0	136.8	150	N/A	N/A	208.0	190.0	179.0	150	N/A	N/A	208.0	190.0	179.0																																																																																																																																																																																																																																																