

New & Improved design includes Independent Drive Motors, Regenerative Dynamic Braking, Power Steering and a Suspension System

75,000 lb Towing Capacity



Standard Features:

- Power steering
- Heavy duty long life torque hubs
- Regenerative dynamic motor braking
- Redundant hydraulic service foot brake
- Automatic parking brake
- Controlled acceleration & deceleration joystick operated throttle
- 2 - 8 Hp continuous duty drive motors coupled directly to brake/torque hub results in fewer moving parts
- Proportional drive with steering position sensor
- Suspension system
- Fully automated, multi-tap battery charger (indicate required frequency) JP-204-50 (50 Hz) or JP-204-60 (60 Hz)
- Battery charge indicator with hourmeter
- 16 - 6 volt batteries
- Reduced tire wear
- Solid rubber tires
- Wheel tie down strap
- Nylon winch strap
- Nylon strut straps
- Sealed winch tension safety switch with no mechanical linkage
- Emergency safety cut off switch
- Hydraulic system filtration
- Covered storage compartments with rubberized coating on aluminum diamond deck cover
- Fire extinguisher
- Headlights
- Rear facing lights
- Strobe light
- Side marker lights
- Horn
- Finish: Durable Powder Coat Tronair Blue

Optional Equipment:

- Aircraft adapters
- Pintle hitch (rear)
- Battery watering system
- Custom colors and graphics

Specifications:

Model Number	Max Aircraft Weight	Cradle Capacity	Speed Empty	Speed Full Load	Length	Width	Height	Weight
lb (kg)	lb (kg)	mph (kph)	mph (kph)	in (cm)	in (cm)	in (cm)	lb (kg)	
JP75	75,000 (34,019)	7,500 (3,402)	8 (12.9)	3 (4.8)	179.5 (455.9)	58 (147.3)	52 (132.1)	5,700 (2,586)

www.tronair.com

Tronair • Email: sales@tronair.com • Phone: 419-866-6301 or 800-426-6301 • Fax: 419-867-0634

Asia Sales Offices: China - Email: tronairchina@tronair.com • Phone: 86-592-5560735 • Fax: 86-592-5563132

Asia/Australia - Email: tronairasia@tronair.com • Phone: 662 2121463 • Fax: 662 2121332

Europe, Middle East & Africa Sales Office • Email: saleseurope@tronair.com • Phone: 44-0-113-245-3300 • Fax: 44-0-113-322-0436

TR030811