Certified Nitrogen Gauges and Regulators

Certified Gauges Mean Smooth Landings And Take Offs

Standard Features:

- Certification documents are provided with all gauges
- Service gauges are protected by a rubber boot
- Service gauges are liquid filled to maintain accuracy
- Storage case standard

14-6833-6030

14-6829-6000

14-6808-6000

14-6806-6011

14-6805-6010

14-6903-6000

14-6895-6000

14-6830-6012

14-6831-6010

14-6807-6011

14-6804-6000

TR021210

visit tronair.com for detailed information

TRONAIR

Wheel, Brake and Strut Servicing

Service you wheels, brakes and struts quickly and efficiently

Tronair, Inc. - 1740 Eber Road, Holland, Ohio 43528, USA
Email: sales@tronair.com • Fax: 419-867-0634
Phone: 419-866-6301 • Toll Free: 1-800-426-6301

Asia Sales Offices
China - Email: tronairchina@tronair.com • Phone: 86-592-5560735 • Fax: 86-592-5563132
Asia/Australia - Email: tronairasia@tronair.com • Phone: 66-2665-6511 • Fax: 66-2204-1858

Europe, Middle East and Africa Sales Office
Email: saleseurope@tronair.com • Phone: 44-0-113-245-3300 • Fax: 44-0-113-322-0436

visit tronair.com for detailed information

Dollies

What once took two men, now takes one

Wheel and Brake Dolly

Service Your Wheels And Brakes Efficiently

Standard Features:

- Accommodates tire sizes from 24 to 54 in (61 to 137 cm)
- Sturdy welded steel construction
- Manually operated hydraulic hand pump
- 7 in (18 cm) maximum lift height
- Adjustable rear swivel caster for tilting the dolly
- Front swivel casters with floor locks
- Padded brake handling adapter
- 84 in (213 cm) strap assembly for securing load to dolly
- 700 lb (318 kg) maximum load capacity
- Finish: Powder Coat Tronair Blue

14-6883-0110

Wheel Dolly

Transport Wheels With Ease

Standard Features:

- Heavy duty 8 in (20 cm) casters
- Sturdy welded steel construction
- Manually operated with hand crank
- 5" diameter swivel casters for greater maneuverability in all directions
- 12" corrosion resistant steel rollers with ball bearings
- Distance between rollers:
  Minimum: 10 in (25.4 cm)
  Maximum: 24 in (60.96 cm)
- Universal applications
- 350 lb (159 kg) maximum load capacity
- Finish: Powder Coat Tronair Blue

14-6909C0000
(wheel not included)

Strut Service Tool

No more removing wheels to exercise struts

Standard Features:

- Safe and efficient
- 1,500 lb (680 kg) capacity
- Safely exercise aircraft landing gear struts to expel air while servicing them with oil
- Reduces the possibility of damage to the aircraft pneumatic lifting operation
- Low profile to fit under most aircraft wings
- Preferred over other methods of strut servicing
- Standard adapter fits most aircraft including Falcons, Challengers & Learjets
- Finish: Durable Powder Coat Tronair Blue

14-6906-0100

Adapter Kits:

K-4126 - Includes kits K-4127, K-4128, K-4129 and K-4130
K-4127 - Axle Adapter Assembly (3.340 diameter) for Gulfstream GII, GIII, GIV, GIVSP, G400
K-4128 - Axle Adapter Assembly (3.536 diameter) for Gulfstream GII, GIII, GIV, GIVSP, G400
K-4129 - Axle Adapter Assembly (3.610 diameter) for Gulfstream GV, GVSP, G350, G450, G500, G550
K-4130 - Axle Adapter Assembly (3.840 diameter) for Gulfstream GV, GVSP, G350, G450, G500, G550

NOTE: Aircraft adapters will vary depending on Gulfstream aircraft model and aircraft service change 155

Universal Tool - Strut, Break and Tire

One tool to service struts, brakes and tires

Standard Features:

- Bombardier approved
- Low profile
- Relief valve to prevent lifting aircraft
- No need to remove tire when servicing struts
- Fits 14" to 30" tire
- 800 lb (362.9 kg) lifting capacity
- Lift range: Collapsed 4.75 in (12 cm)
  Fully extended 21 in (53.34 cm)
- Long handle for ease of lifting
- Wide, heavy duty steel turntable for both nose and main tires
- Easy clamp to lock tire in place
- 2 swivel casters for easy maneuverability
- No mark rubber wheels
- Finish: Powder Coat Tronair Blue

Extended
(wheel not included)

14-6911-0100
Collapsed

visit tronair.com for detailed information